

Test Report

No. 2853627/TX Date: May 09 2007

Page 1 of 2

AJM Shopping Limited Unit 1, Park Springs Springvale Road Grimethorpe Barnsley, S72 7BQ

The following sample was submitted and identified on behalf of the buyer as:

One sample of woven satin lining cutting for 3x3M, 4x4M, 5x5M, 6x6M, 8x8M, 10x10M tent pagoda and 3M/6M/9M/10M/12M/15M/20M/25M gala tent modulas (100% polyester) in cream / ivory.

Country Of Destination : U.K.

Sample Receiving Date : Apr 24, 2007

Test Performing Date : Apr 25, 2007

Test Performed : Selected test(s) as requested by applicant.

* * * *

Test Results : Please refer to the next page(s).

Residual sample returned to applicant

Signed for and on behalf of SGS Hong Kong Ltd.

Leung Po Ling, Cali Senior Account Executive

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. Unless otherwise stated: (a) the results shown in this document refer only to the sample(s) resteted and (b) such sample(s) are retained for 30 days only. This document nonot be reproduced except in full, without prior approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law.



Test Report No. 2853627/TX Date: May 09 2007 Page 2 of 2

Test Results:

Flammability Test (BS 5867:1980 Part 2 Type B / BS 5438 : 1976 Test Method 2)

Lancasta de la contra dela contra de la contra del la contra del la contra del la contra de la contra del la contra de la contra de la contra del la cont

As Received

	<u>Lengthwise</u>			Widthwise		
Specimen	(1)	(2)	(3)	(1)	(2)	(3)
Flame reached an edge	Ν	Ν	Ν	Ν	Ν	Ν
Hole reached an edge	Ν	Ν	N	N	Ν	Ν
Flaming debris	Ν	Ν	Ν	Ν	Ν	Ν
Maximum vertical extent						
of hole (mm)	34	33	48	27	44	29
Maximum horizontal extent						
of hole (mm)	16	21	29	19	22	20
Duration of flaming (sec.)	0	0	0	0	0	0
Duration of afterglow (sec.)	0	0	0	0	0	0

Requirement : (1) No any part of any hole or any part of the lowest boundary of any

flame reaches the upper edge or either vertical edge of more than

one of six specimens.

(2) No any separation of any flaming debris from more than one of

six specimens.

Remarks: : Y: Yes

N: No

Flame application time : 15 seconds

Note : The result may not apply to situations where there is restricted air supply

or prolonged exposure to large sources of intense heat as in a

conflagration.

Comment : The submitted sample complies with the requirements for type B

of BS 5867:1980 Part 2.

*** End of Report ***

This document is issued by the Company subject to its General Conditions of Service printed overleaf or available on request and accessible at www.sgs.com. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. Unless otherwise stated: (a) the results shown in this document refer only to the sample(s) tested and (b) such sample(s) are retained for 30 days only. This document cannot be reproduced except in full, without prior approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful and offenders may be prosecuted to the fullest extent of the law.